TAKASAGO CHAIN

ON ROAD CHAINS

RK ZXW Premium High Performance - XW Seals

ZXW Series Chains are the strongest, longest-lasting premium quality XW-Ring equipped chain available on the market today! ZXW is ideal for high-speed, high-horsepower performance applications.

RK GXW Series Chains - XW Seals

RK's GXW series chains are the top of the line extreme performance chains. XW-ring chains are the BEST high-speed, extreme heat performance chains available today. GXW chains provide up to 10 times longer wearlife compared to standard chains.

RK XSO Series Chains - RX Seals

Affordable, long lasting performance RX sealed chain. XSO series offer less torsional friction and increased performance. XSO chains provide up to 7 times longer wearlife compared to standard chains.

RK SO Series Chains - O Seals

RK's traditional round "O" ring chain is a convenient blend of performance and affordability. 520SO chains are suitable for low to mid-range CC motorcycles that came from the factory with sealed chains.

OFF ROAD CHAINS

RK MXZ4 Heavy Duty MX Race Chain

MXZ4 is one of the lightest motocross chains available on the market today. Made for the professional motocross racer, MXZ4 is the next generation of motocross racing chains featuring Chromoly steel construction and seamless rollers and bushings.

RK MXU Sealed MX Chain

Combines both longevity and performance. MXU is one of the lightest sealed-ring motocross chains available on the market today. MXU features Ultra-thin UW-Seals perfect for bikes with case clearance issues.

RK EXW Sealed ATV/Off-Road Chain

EXW is specifically designed for ATV/Off-Road vehicles and is the best high-speed, extreme heat, off-road performance chain available. EXW chains feature XW-Ring seals to better survive the abrasive conditions that exist in hostile off-road conditions.

RK MALAYSIA

RKM Heavy-Duty Chain

Heavy Duty, non-sealed motorcycle chain for small CC motorcycles that did not come from the factory with a sealed chain. When choosing RKM chains, please make sure the chain you choose has a suitable CC rating for the CC's of your motorcycle.

RKM Standard Chain

Economically priced, non-sealed motorcycle chain for small CC motorcycles that did not come from the factory with a sealed chain. When choosing RKM chains, please make sure the chain you choose has a suitable CC rating for the CC's of your motorcycle.






















Non "O" Ring vs Basic O'Ring

 A properly lubricated, Heavy Duty racing non-O'Ring chain will perform efficiently as long as there is a "lubricating oil boundary layer" between critical bearing surfaces. However, once the boundary layer dissipates from high speed running, lack of maintenance, or simply over time, the inner bearing surfaces will overheat, kink, cause severe drag, and ultimately fail. RK O'Ring chains prevent this from happening by continuously lubricating and protecting critical internal bearing surfaces.



• The standard RK O'Ring has a flat contact patch that holds the lubrication in place. The result is a smooth transfer of power - quietly, safely and efficiently - with absolutely no O'Ring drag, plus the benefit of three times the wear life of a standard non O'Ring chain.


REMEMBER: If your motorcycle came from the factory with an O'Ring chain, it should always be replaced with an O'Ring chain.

RX" - Ring Design and Features

RK's "RX-ring" chains feature an X-ring shaped seal. Viewed in cross-section, the "X-ring" has two
lubrication pools and seal points versus the single seal point/pool design of a regular o-ring chain.
 "RX-ring" technology offers less torsional friction, increased high-stress performance, and a 30% longer
 wear life compared to standard o-ring chains. RK's new "RX-ring" chains offer tremendous value, plus true
 quality and performance for all but the most demanding high performance applications.

"XW"-Ring Design and Features

• The leading edge "XW"-Ring is the ultimate high speed, extreme heat performance chain. The XW-Ring is made of an advanced Nitrile Butadiene composite and is equipped with three contact lips and two convex outer stabilizers. This means three lubrication pools to protect against high speed abrasion, extreme heat build up, torsional flex and the loss of lubricant under these extreme conditions. The Nitrile Butadiene composite is oil and contaminant resistant, and the "XW" design is compression and distortion resistant to provide the ultimate in efficiency and performance. The XW-Ring goes the distance to fully eliminate the risk of seal failure and provides the user with a 50% longer wear life than the basic O'Ring chain; plus a 20% increase over other competitive "X"-Ring type chains.







"O"-Ring

Cut-Away

XW RING CUTAWAY



2018 RK CHAIN APPLICATIONS															
CHAIN	NATURAL	GOLD	COLOR	SEAL	STREET	OFF-ROAD	МХ	RACE	ATV	TENSILE** (Ibs)	MAX HORSE POWER	Fatigue (Ibs)	WEAR	WEIGHT* (Ibs)	MAX CHAIN WIDTH *** (mm)
STRONGEST ON	THE STREE	ET						8 - C							
520ZXW		~	~	xw	1200					9,450	200 HP	2181	3800	3.92	20.8
525ZXW		~	~	XW	1300					10,430	220 HP	2650	4100	4.56	23.4
530ZXW		~	~	xw	1400					11,200	220 HP	2650	4200	4.89	25.4
STRONG & DURA	ABLE HIGH	PERFORM	ANCE STR	EET & O	FF ROAD	8									
520GXW	~	1	~	xw	1200	750		1200		8,700	200 HP	2180	3750	3.70	20.8
525GXW	~	~	~	XW	1300	800		1300		8,900	200 HP	2200	3900	4.13	22.9
530GXW	~	~	~	xw	1400	900		1400		9,900	205 HP	2650	4050	4.65	24.5
LIGHT WEIGHT H	IGH PERFO	RMANCE	STREET &	OFF RO	AD										
428XSO	~	1		RX	400	350				5,280	60 HP	1530	2700	2.65	22.3
520XSO	~	~	~	RX	750	750			750	8,300	80 HP	2180	3500	3.44	21.7
525XSO	~	~		RX	900	750				8,400	150 HP	2200	3700	4.13	22.9
530XSOZ1	~	~	~	RX	1000	750				9,000	150 HP	2430	3900	4.36	24.5
ECONOMICAL SE	ALED STR	EET													
520SO	~			0	400					6,900	60 HP	1710	2400	3.39	21.7
OFF ROAD / ATV	RACE SPE	CIFIC													
520EXW	~	~		xw		750		750	750	7,700	70 HP	1930	3300	3.70	22.0
OFF ROAD / END	URO RACE	SPECIFIC							_						2
520MXU		~		UW		500	500	500		8,000	70 HP	1930	3200	3.04	19.1
PRO MX / SX RAG	E SPECIFIC	- MXZ4 S	Series com	es with H	ard chron	ne Coatin	g pin with	Extended	d wear life			9			
420MXZ4		~				150	150	150		5,400	40 HP	970	450	1.83	17.8
428MXZ4		1	1			150	150	150		6,100	40 HP	1460	450	2.21	20.1
520MXZ4	~	1	~			500	500	500		8,000	70 HP	2180	450	3.02	18.8
WEEKEND WARF	RIOR MX / S	x			_		_				10 10				
420MXZ	~	~				150	150	150		4,980	30 HP	880	200	1.73	17.1
428MXZ	1	~				150	150	150		5,800	30 HP	1215	200	2.09	18.9
HEAVY DUTY						_		11 - 11 11							
M415H	~				125	80		· ·		4,100	50 HP	970	200	1.59	14.6
M420H	~				125	90				4,100	15 HP	970	200	1.79	16.9
M428H	~				200	125				5,400	15 HP	1215	200	2.22	20.3
M520H	~		1.1		400	250			1	7,700	30 HP	1930	200	3.51	19.7
M525H	~				500					7,700	40 HP	1930	200	3.73	21.3
M530H	~			- 2	500					7,700	40 HP	1930	200	4.17	22.9
530KS	~		-		400					7,100	60 HP	1930	200	3.75	21.9
STANDARD				_										1	
M420	~				125	90	1			4,000	10 HP	970	100	1.65	16.2
M428	~				150	125			1	4,500	12 HP	970	100	1.85	18.9
M520	~				250	250				6.800	20 HP	1460	100	3.28	18.5
M525	~				400					6,800	30 HP	1460	100	3.51	19.9
M530	~				400					6,800	30 HP	1460	100	3.73	21.7
RK recommends u * = LBS/100 Links ** = LBS/FT	K recommends using a chain model with the maximum amount of displacement and horsepower ratings based on motorcycle's original equiped chain size. = LBS/100 Links														

** = LBS/FT *** = LBS/FT ***= Need a wider amount of space than the maximum chain width in order to install the chain.





All chains come complete with master link. Links are sold individually.

415 Malavsia S	tandard Chain Link		
PART #	DESCRIPTION	CLIP/RIVET	
225-415	415 Connecting Link	Clip	
115 Malaycia H	leavy Duty Chain		
• Tensile Strength:			
PART #	DESCRIPTION	CLIP/RIVET	PK Charles
225-415H	415H Connecting Link		TAKASAGO CHAIN
225-415H-110	415H x 110 Links	Clip	A15H
223-4158-110	415H X 110 LINKS	Clip	PRI EGE CO.JTD.
420 Malaysia R	K Chain		
Standard Chai	n		
• Tensile Strength 4	100 lbs/ft.		
PART #	DESCRIPTION	CLIP/RIVET	
225-420	420 Connecting Link	Clip	Motorcycle Chain
225-420-120	420 x 120 Links	Clip	420
225-420-134	420 x 134 Links	Clip	New LIKEL CO., LTD., JAPAN
420 MX74 - Evt	ra Heavy Duty Motoc	•	
Tensile Strength		Cost nating chall	
Wearlife Index 300			RK White
PART #	DESCRIPTION	CLIP/RIVET	RATE OFFICE
225-420MXZ	420MXZ Connecting Link	Clip	428MX7
225-420MXZ-120	420MXZ x 120 Links	Clip	PREMIEW MOTOCOSS RACING CHAIN
225-420MXZ-134	420MXZ x 134 Links	Clip	NK DEL CO_LTD.
GOLD Inner and O	uter Plates		RK WEEK
225-GB420MXZ	GB420MXZ Gold Connecting	g Link Clip	HEAT BUT
225-GB420MXZ-120	GB420MXZ x 120 Links Gold	d Clip	GB42UMXZ
225-GB420MXZ-126	GB420MXZ x 136 Links Gold	d Clip	PELMELW MOTOCROSS BACENS CIELIN RHK EXCELCO., LTD.
420 SO Chain			
SO O'Ring Chai	n		
Tensile Strength:			
Wearlife Index: 400			TAKASAGO CHAN
PART #	DESCRIPTION	CLIP/RIVET	120000
225-42050	420SO Connecting Link	Clip	42050
225-42050-136	42050 x 136 Links	Clip	HAL 1028, (0.17).
		-inh	
428 Malaysia S	tandard Chain		
• Tensile Strength 4			
PART #	DESCRIPTION	CLIP/RIVET	RKCACA
225-428	428 Connecting Link	Clip	TAKASAGO CHAIN Motorcycle Chain
225-428-124	428 x 124 Links	Clip	428
225-428-134	428 x 134 Links	Clip	RK EXEL CO., LTD., JAPAN
428 Malaysia H	leavy Duty Chain		
• Tensile Strength 4			
PART #	DESCRIPTION	CLIP/RIVET	
225-428H	428H Connecting Link	Clip	RK Check
225-428H-110	428H x 110 Links	Clip	TAKASAGO CHAIN Heavy Duty Chain
225-428H-120	428H x 120 Links	Clip	428H
225-428H-134	428H x 134 Links	Clip	RK JAPAN CO., LTD.
		·	

Chain

	RK	DRIVE C	HAIN
428 MXZ4 - Extra	a Heavy Duty Motocross	Chain	
• Tensile Strength 610	0 lbs/ft		
PART #	DESCRIPTION	CLIP/RIVET	
225-428MXZ	420MXZ Connecting Link	Clip	The second sec
225-428MXZ-122	428MXZ x 122 Links	Clip	
225-428MXZ-126	428MXZ x 126 Links	Clip	RK
225-428MXZ-134	428MXZ x 134 Links	Clip	CR428MXZ
GOLD Inner and Out			
225-GB428MXZ	GB428MXZ Gold Connecting Link		
225-GB428MXZ-122	GB428MXZ x 122 Links Gold	Clip	
225-GB428MXZ-126	GB428MXZ x 126 Links Gold	Clip	
428 SO Chain Cl			
PART #		CLIP/RIVET	
225-42850	428SO Connecting Link	Clip	
520 Malaysia Sta	andard Chain - not recomm	nended for off-ro	oad use
• Tensile Strength: 6			
PART #	DESCRIPTION	CLIP/RIVET	TAKASAGO CHAIN
225-520	520 Connecting Link	Clip	Motorcycle Chain
225-520-120	520 x 120 Links	Clip	520
520 Malaysia Ha	Duty Chair		NR EXILCOLITO, JAPAN
 520 Malaysia He Tensile Strength: 7 			
225-520H	520H Connecting Link	Clip	RK Sector
225-520H-120	520H x 120 Links	Clip	TAKASAGO CHAIN Heavy Duty Chain
		chp	520H
	ATWOff Deed Chain		PHK DKIL CO.LTD., JAPAN
• Tensile Strength: 77	ATV/Off-Road Chain		
• Tensile Strength: // PART #		CLIP/RIVET	
225-520EXW	520EXW Connecting Link	Clip	
225-520EXW-110	520EXW connecting Link 520EXW x 110 Links	Clip	RK WAR AS
225-520EXW-110	520EXW x 120 Links	Clip	Theory Course
225-520EXW-120	520EXW x 120 Links	Clip	520EXW 5267
GOLD Inner and Out		chp	PREMILM ATV & OFF-ROAD CHAIN
225-GB520EXW-120	520EXW x 120 Links Gold	Clip	WK EXCLOULTD.
225-GB520EXW-130	520EXW x 130 Links Gold	Clip	
520 GVW Sovies	Chains - XW Seals		
Tensile Strength 88			
PART #		CLIP/RIVET	
225-520SM	520SM Connecting Link	Clip	
225-520SMO-R	520SMO Connecting Link	Rivet	TAKASAGO CHAIN
225-520GXW	520GXW Connecting Link	Rivet	520GXW
225-520GXW-120	520GXW x 120 links	Rivet	
225-4987	520GXW x 120 links Black Scale	Rivet	Being the best is a commitment
GOLD Inner and Out			
225-GB520GXW-120	GB520GXW x 120 Links Gold	Rivet	
520 MXU Sealed			
Tensile Strength 80			
	ation retaining grooves		
PART #		CLIP/RIVET	RK WEBS
225-4477	520MXU x 120 links Green	Clip	UW-RING
GOLD Inner and Out			GB520MXU 🔍
225-GB520MXU	GB520MXU Connecting Link Gold		PREMIUM OFF-ROAD STATED CRAIN
2250GB520MXU-114	GB520MXU x 114 Links Gold	Clip Clip	THE SALLOWLER.
225-GB520MXU-120	GB520MXU x 120 Links Gold	Clip	

www.Trans Can Imports.com ^{.....} 1-800-661-9438



All chains come complete with master link. Links are sold individually.

520 MXZ4 Heav	y Duty MX Race Chain		
Tensile Strength: 8			
PART #	DESCRIPTION	CLIP/RIVET	DK
225-520MXZ	520 Connecting Link	Clip	HANT DATY
225-520MXZ-120	520MXZ4 x 120 Links	Clip	520MY7
225-520MXZ-130	520MXZ4 x 130 Links	Clip	PEMIEN NOTOCROSS EALENC CHAIN
GOLD Inner and Out	ter Plates	- F	PKK EKCL CO., LTD.
225-GB520MXZ	GB520 Connecting Link Gold	Clip	
225-GB520MXZ-116	GB520MXZ4 x 116 Links Gold	Clip	
225-GB520MXZ-120	GB520MXZ4 x 120 Links Gold	Clip	
520 SO Series C	hains - O Seals		
• Tensile Strength: (5900 lbs/ft.		
225-520SO	520SO Connecting Link	Clip	TAKASAGO CHAN
225-520SO-090	520SO x 90 Links	Clip	0-Ring Chain
225-520SO-110	520SO x 110 Links	Clip	
225-52050-120	520SO x 120 Links	Clip	Being the best is a commitment
520 XSO Series	Chains - RX Seals		
• Tensile Strength: 7	700 lbs/ft.		
PART #	DESCRIPTION	CLIP/RIVET	
225-520XSO	520XSO Connecting Link	Clip	
225-520XSO-R	520XSO Connecting Link	Rivet	TAKASAGO CHAIN
225-520XSO-090	520XSO x 090 Links	Rivet	BX-Bing Ghain
225-520XSO-110	520XSO x 110 Links	Rivet	
225-520XSO-114	520XSO x 114 Links	Rivet	Being the best is a commitment
225-520XSO-120	520XSO x 120 Links	Rivet	
225-520XSO-130	520XSO x 130 Links	Rivet	
• GOLD Inner and Out	ter Plates		RX-Ring Chain
225-GB520XSO	520XSO Connecting Link Gold	Clip	
225-GB520XSO-110	520XSO x 110 Links Gold	Rivet	GB520XS0
225-GB520XSO-114	520XSO x 114 Links Gold	Rivet	
225-GB520XSO-120	520XSO x 120 Links Gold	Rivet	
520 ZXW PREMI	UM HIGH PERFORMANC	E	
• Tensile Strength 94	450 lbs/ft.		ANT ORDER TO BELLEVILLE
PART #	DESCRIPTION	CLIP/RIVET	
225-520ZXW-120	520ZXW x 120 links	Rivet	



225-520KZ	520KZ6 Dirt Bike Connecting Link	Clip
225-520KZ-120	520KZ6-120 links Dirt Bike Chain	Clip
GOLD Inner and Outer	r Plates	
225-GB520KZ	GB520KZ6 Connecting Link Gold	Clip
225-GB520KZ-120	GB520KZ6x 120 Links Gold	Clip



CLIP/RIVET



All chains come complete with master link. Links are sold individually. S25 Malaysia Standard Chain - not recommended for off-road use • Tensile Strength: 6600 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525 525 Connecting Link Clip 225-525-120 525 x 120 Links Clip S25 Malaysia HD Chain • Tensile Strength: 7700 lbs/ft. PART # DESCRIPTION CLIP/RIVET S25 Malaysia HD Chain • Tensile Strength: 7700 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525H 525H connecting Link Clip S25 GXW Series Chains - XW Seals • Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525GXW • Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET • Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET • Tensile Str
S25 Malaysia Standard Chain - not recommended for off-road use • Tensile Strength: 6600 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525 525 Connecting Link Clip Description 225-525-120 525 x 120 Links Clip Description 525 Malaysia HD Chain • Tensile Strength: 7700 lbs/ft. PART # DESCRIPTION CLIP/RIVET • Tensile Strength: 7700 lbs/ft. PART # DESCRIPTION CLIP/RIVET Description 225-525H 525H Connecting Link Clip Clip Description 225-525H 525H Connecting Link Clip Description Description 225-525H 525H Connecting Link Clip Description Description 225-525H 525H x 120 Links Rivet Description Description 525 GXW Series Chains - XW Seals • • • • • Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET Description • Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET Description • Z25-525GXW 525GXW Connecting Link Rivet Descri
 Tensile Strength: 6600 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525 525 525 525 Connecting Link Clip 225-525-120 525 x 120 Links Clip 525 Malaysia HD Chain Tensile Strength: 7700 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525H 525H connecting Link Clip 225-525H 525H connecting Link Clip 525 Malaysia HD Chains 525 GXW Series Chains - XW Seals Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET 525 GXW Series Chains - XW Seals Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525GXW 525GXW Connecting Link Rivet
 Tensile Strength: 6600 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525 525 525 Connecting Link Clip 225-525-120 525 x 120 Links Clip CLIP/RIVET Tensile Strength: 7700 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525H 525H connecting Link Clip 225-525H 525H connecting Link Clip S25 GXW Series Chains - XW Seals Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET S25 GXW Series Chains - XW Seals Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET S25 GXW Series Chains - XW Seals
PART #DESCRIPTIONCLIP/RIVET225-525525 Connecting LinkClip225-525-120525 x 120 LinksClipS25 Malaysia HD Chain• Tensile Strength: 7700 lbs/ft.PART #DESCRIPTIONCLIP/RIVET225-525H525H Connecting LinkClip225-525H525H connecting LinkRivetSEE Chains - XW Seals• Tensile Strength: 9300 lbs/ft.PART #DESCRIPTIONCLIP/RIVETCLIP/RIVET225-525GXW525GXW Connecting LinkRivet
225-525525 Connecting LinkClip225-525-120525 x 120 LinksClipS25 Malaysia HD Chain• Tensile Strength: 7700 lbs/ft.PART #DESCRIPTIONCLIP/RIVET225-525H525H Connecting LinkClip225-525H525H Connecting LinkClip225-525H-120525H x 120 LinksRivetS25 GXW Series Chains - XW Seals• Tensile Strength: 9300 lbs/ft.PART #DESCRIPTIONCLIP/RIVETCLIP/RIVET225-525GXW525GXW Connecting LinkRivetCLIP/RIVET225-525GXW525GXW Connecting LinkRivetCLIP/RIVET
225-525-120525 x 120 LinksClip525 xS25 Malaysia HD Chain• Tensile Strength: 7700 lbs/ft.PART #DESCRIPTIONCLIP/RIVET225-525H525H Connecting LinkClip225-525H-120525H x 120 LinksRivetS25 GXW Series Chains - XW Seals• Tensile Strength: 9300 lbs/ft.PART #DESCRIPTIONCLIP/RIVET225-525GXW525GXW Connecting LinkRivet
 Tensile Strength: 7700 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525H 525H Connecting Link Clip 225-525H-120 525H x 120 Links Rivet S255 GXW Series Chains - XW Seals Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525GXW 525GXW Connecting Link Rivet
 Tensile Strength: 7700 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525H 525H Connecting Link Clip 225-525H-120 525H x 120 Links Rivet S255 GXW Series Chains - XW Seals Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525GXW 525GXW Connecting Link Rivet
PART # DESCRIPTION CLIP/RIVET 225-525H 525H Connecting Link Clip 225-525H-120 525H x 120 Links Rivet S255 GXW Series Chains - XW Seals • Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525GXW 525GXW Connecting Link Rivet
225-525H 525H Connecting Link Clip 225-525H-120 525H x 120 Links Rivet 5255 GXW Series Chains - XW Seals • Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525GXW 525GXW Connecting Link Rivet
225-525H 525H connecting Link Clip 225-525H-120 525H x 120 Links Rivet 525 GXW Series Chains - XW Seals • Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525GXW 525GXW Connecting Link
525 GXW Series Chains - XW Seals • Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION 225-525GXW 525GXW Connecting Link
Tensile Strength: 9300 lbs/ft. PART # DESCRIPTION CLIP/RIVET 225-525GXW 525GXW Connecting Link Rivet
PART # DESCRIPTION CLIP/RIVET 225-525GXW 525GXW Connecting Link Rivet
PART # DESCRIPTION CLIP/RIVET 225-525GXW 525GXW Connecting Link Rivet
O D D D D D D D D D D D D D D D D D D D
225-525GXW-120 525GXW x 120 links Rivet GB525GXW
225-525GXW-130 525GXW x 130 links Rivet
GOLD Inner and Outer Plates
252-GB525GXW-120 GB525GXW x 120 links Gold Rivet
525 XSO Series Chains - RX Seals
Tensile Strength 8400 lbs/ft.
PART # DESCRIPTION CLIP/RIVET
225-525XSO 525XSO Connecting Link Clip
225-525XSO-R 525XSO Connecting Link Rivet 525XSO
225-525XSO-110 525XSO x 110 Links Rivet
225-525XSO-120 525XSO x 120 Links Rivet
225-525XSO-122 525XSO x 122 Links Rivet
225-525XSO-130 525XSO x 130 Links Rivet
• GOLD Inner and Outer Plates GB525XSO GB525XSO GB525XSO
225-GB525XSO GB525XSO Connecting Link Gold Clip
225-GB525XSO-120 GB525XSO x 120 Links Gold Clip
525 ZXW PREMIUM HIGH PERFORMANCE
• Tensile Strength 10,430 lbs/ft.
PART # DESCRIPTION CLIP/RIVET
225-525ZXW-120 525ZXW x 120 links Rivet
RAD BACE
530 Malaysia Standard Chain
Tensile Strength 6600 lbs/ft.
PART # DESCRIPTION CLIP/RIVET
225-530 530 Connecting Link Clip
225-530-120 530 x 120 Links Clip 530

Heavy Duty Chain

 Tensile Strength 	6800 lbs/ft.
PART #	DESCRIP
225-530H	530H Coi
225-530H-120	530H x 1

CLIP/RIVET Clip Clip







All chains come complete with master link. Links are sold individually.

	Chains - XW Seals		
• Tensile Strength: 1			
Wearlife Index 1000			
225-530GXW	530GXW Connecting Link	Rivet	XW-Ring Chain
225-530GXW-110	530GXW x 110 Links	Rivet	JEUGAW
225-530GXW-120	530GXW x 120 Links	Rivet	and a second sec
 GOLD Inner and Out 			RES XW-Ring Chain
225-GB530GXW-110	GB530GXW x 120 links Gold	Rivet	
530 XSOZ1 Serie	es Chains - RX Seals		
• Tensile Strength 90	000 lbs/ft.		
CONNECTING LINK #		CLIP/RIVET	
• Fits Pre 2007 Chains			
225-530XSO-C2	(fits pre 2007 chains)	Clip	
225-530XSOZR		Rivet	
• Fits 2007 and Newe	r Chains		
225-530XSO-C1		Clip	
225-530XSO-R		Rivet	BX-Bing Ehelp
PART #	DESCRIPTION	CLIP/RIVET	530XS021
225-530XSO-106	530XS0 x 106 Links	Rivet	The BY Black Chain
225-530XSO-110	530XS0 x 110 Links	Rivet	and the training of the traini
225-530XSO-114	530XS0 x 114 Links	Rivet	
225-530XSO-120	530XS0 x 120 Links	Rivet	
GOLD Inner and Out	ter Plates		
225-GB530XSO	GB530XSO Connecting Link - G	old Rivet	
225-GB530XSO-120	GB530XSO x 120 Links Gold	Rivet	
530 KS Street C	hain		
• Tensile Strength: 8	8000 lbs/ft.		
225-530KS	530KS Connecting Link	Clip	RK Charles
225-530KS-120	530KS x 120 Links	Clip	530(50)KS
		Limited Stock	MI ME DA LAS







630 - Connecting links

PART # **Sef** 630SO 225-630SO-R 225-630GSV

DESCRIPTION 630SO Connecting Link 630SO Connecting Link 630GSV Connecting Link

CLIP/RIVET Clip Rivet Clip



632 GSV Premium XW-Ring Chain DESCRIPTION

PART # 225-632GSV-094

632GSV x 120 links

CLIP/RIVET Rivet



EK CHAIN & CONNECTING LINKS

	MOTORCYCLE CHAIN	ALL OD O	X
Chain	Tensile (lbs)	Max cc/hp	Wear Life

	(lbs)		Index
520	7400	250 сс	100
520SR	7700	350 cc	200
520SRO	7400	100 cc	800
530	7400	350cc	100

SPORT/GRADE

SPORT/GRADE Heavy Duty **O-Ring** non-sealed Heavy Duty O-Ring

CHAIN

228-630MS

228-630MS-R

PART # DESCRIPTION 228-520SR-090

520SR x 90 Links non-sealed Heavy Duty

Connecting Link				
Sport Series				
PART #	DESCRIPTION			
228-520SR	520SR Clip			
228-520SROZ	520ROZ Clip			
228-530	530 Clip			
228-530SR	530SR Clip			
228-530SROZ	530SROZ Clip			
228-630SRO	630SRO Clip			
228-630SRO-R	630SRO Rivet			
Super Sport Series				
PART #	DESCRIPTION			
228-520MRD	520MR Gold Clip			
228-530MVX	530MVX Clip			
228-530MVX-R	530MVX Rivet			

	O-Ring O-Ring
)	SPORT/GRADE Heavy Duty
	Heavy Duty O-Ring Heavy Duty O-Ring
	Heavy Duty Heavy Duty

TYC CHAINS

• Premium Grade - High quality at an excellent price. Chains feature thicker side plates for greater strength and longer life.

• O-Ring - Bullet proof performance for all O-Ring applications.

630MS Clip

630MS Rivet

PART #	DESCRIPTION
227-428H	Premium 428 Connecting Link
227-525H	Premium 525 Connecting Link
227-525H-122	Premium 525 Chain x 122 Link
227-530H	Premium 530 Connecting Link



5/8" x 1/4"

PXW